Alpha MAC Setup Guide

Cubase LE Setup

When using the Alpha with Cubase LE, it will be best to set the Alpha as the default audio device under the MAC OS utility "Audio MIDI Setup".

1. Go to the main applications folder and choose the Utilities folder.

2. Start the Audio/MIDI Setup utility application.

3. Set "Lexicon Alpha In/Out" for the Default Input, Default Output and System Output settings.

0	0						Audio M	IDI S	etup						
						Audio	Devices	М	IDI Devid	es					
Sys	tem Set	tings	<u>.</u>												
Default Input: 🛛 🖞 Le			exicon Alpha In/Out					Default Output:		🖞 Lexicon Alpha In/Out					
							System Output:		put:	🜵 Lexicon Alpha In/Out					
Pro	perties	For:	₽ Le	xicon	Alpha	In/Ou	t 🛟	- 7							— (
Clock Source: Defau				ilt 🛟				Configure Speakers							
Au	dio Inpu	it —						Au	dio Out	put —					
- ((Master Stream 🕴							Г	Master S	tream			*		
	Source:	Defa	Default +						Source:	Defa	ault 🛟				
Format:		4410	0.0 Hz	•	2ch-24bit		•		Format:		0.0 Hz	•	2ch-2	24bit	•
Ch	h Volume Slider			Value	dB Mute Thr		Thru	Ch	Ch Volume Slider				Value	dB	Mute
м	м 💮 — — — — — — — — — — — — — — — — — —			n/a	n/a		8	м	0			_	n/a	n/a	
1 0			n/a	n/a n/a			1	0			_	n/a	n/a		
1	~				n/a n/a 📃				2 💮						

4. Next, launch the Cubase LE application and choose the section for Devices, Device Setup. Under the VST Multitrack section, choose "Lexicon Alpha In/Out (2)" for the ASIO driver.

Devices	
All MIDI Inputs Default MIDI Ports MIDI System /ST Multitrack	Setup Add/Remove
'ST System Link 'ideo Player	128 KB Disk Buffer Size Lexicon Alpha In/Out (2) ASIO Driver
	Internal Clock Source
	Release ASIO Driver in Background
	1024 Sample Audio Buffer Size
	Expert
	Help Reset Apply
	(Reset All) (Cancel) (OK

5. Click OK.

6. Next, go to Devices, VST Inputs.



- 7. Make sure the inputs for Alpha are set to "Active" (light blue color).
- 8. Cubase LE is now set properly for use with the Alpha.